## **SYMMETRY Product Specifications**

40 Watts

SY2-M40W-5M



The Symmetry range of small area modules are perfect for use in a wide variety of low power solar PV systems. Available in a range of sizes from 5 watts up to 160 watts, the Symmetry range uses mono-crystalline, weatherproof A grade solar cells in a robust aluminium frame.

#### Features:

### ■ High Efficiency

High module conversion efficiency, through innovative manufacturing technology.

## ■ Low-Light Performance

Advanced glass and solar cell surface texturing allow for excellent performance in low-light environments.

#### ■ Severe Weather Resilience


Certified to withstand - wind load (2400Pa) and snow load (5400Pa).

## ■ Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance certified by TUV.

#### ■ 0-+5W Positive Tolerance

Detailed information in Electrical Specifications.



## **Electrical Specifications**

Model Number	SY2-M40W-5M
Peak Power – Pmax (W)	40
Max. Power Voltage – Vmp (V)	18.33
Max. Power Current - Imp (A)	2.19
Open Circuit Voltage – Voc (V)	22.45
Short Circuit Current – Isc (A)	2.31
Cell Efficiency (%)	18.19
Module Efficiency (%)	14.09
Max. System Voltage (V)	1000
Max. Series Fuse Rating (A)	10
Power Tolerance	0 ~ +3%
Pmax Temp. Coefficients (W/ °C)	-0.400%
Voc Temp. Coefficients (V/ °C)	-0.290%
Isc Temp. Coefficients (A/ °C)	+0.048%
NOCT Nominal Operating Cell Temp (°C)	45±2
Operating & Storage Temp. (°C)	-40 ∼ +85
Standard Test Conditions (STC)	1.000w/m²; AM1.6; 25 +/-2 °C

# **SYMMETRY Product Specifications**

40 Watts

SY2-M40W-5M



## **Mechanical Specifications**

Model Number	SY2-M40W-5M
Cell Type	Mono-crystalline
No. of Cells	36 (4x9)
Module Dimensions	550 x 505 x 25mm
Weight	3.1kg
Front Glass	3.2mm high transmission, low iron, tempered glass
Frame	Anodized Aluminium Alloy
Junction Box	IP65 Rated
Output Cable	5m x 1.3mm <sup>2</sup> dual core with tinned cable ends (UV rated)
Carton Dimensions	565 x 540 x 40mm

#### **Product Standards**

Product Performance	IEC61215
Product Safety	IEC61730
Warranty	Workmanship & materials; 5 years

## **Product Dimensions (mm)**

